



### MATERIAL LIST:

⑧	Bottom Panel:	Fireproof PC/ABS UL-94V0(metallized)	1	
⑦	Upper Panel Cover:	Fireproof PC/ABS UL-94V0(metallized)	1	
⑥	RJ-45 JackShield:	0.25mm thickness Brass with Ni plated	2	
⑤	RJ-45 Jack:	Housing-PBT/FTP 8P8C 6u" gold plated	2	
④	PCB:	FR-4/1.6mm UL-94V0	1	
③	Cable:	STP Cable(ivory)	1	
②	Cable boot:	PVC uL-94V0(ivory)	2	
①	Connector:	RJ45 8P8C PLUG GOLD PLATED 3u"	1	
NO.			QT* Y	REMARK

### NOTES:

- Electrical Specifications:
- Insulation Resistance: 500M ohms (min.)
- Contact Resistance: 20M ohms (max.)
- Current Rating : 1.5 Amps.
- DC Resistance: 0.1 ohms(max.)
- Withstanding Voltage : 1000 VAC RMS @ 60Hz/ 1 min.
- Mechanical Specifications:
- RJ-45 Jack Insertion Cycle : Over 200 Cycles (min.)
- PACKING:SYNERGY 21 PE BAG+LABEL

### SYNERGY 21

CUSTOMER		ITEM NO.		S215235	
PRODUCT NAME	ISDN Adapter RJ45 to 215M JACK	Manufacturer country:	CHINA	UNTT	MM
DRAWNBY	CHECKBY	APPROBY	DATE		
SYNERGY 21	SYNERGY 21	SYNERGY 21	2010-03-15		
DATE	REV.				
2010-03-15	A				
REVISION RECORD MODIFICATIONS					
BY	CHK				
		NEW			