



NOTE:

- Electrical test:
 - 100% open short & miss wire test;
 - Insulation resistance:DC 300V 0.01s 10M ohm min;
 - Contact resistance:3 ohm max;
- Computer + Monitor test
 - Resolution:3840*2160@120Hz
- Marking:DisplayPort Cable E***** 兄 AWM STYLE 20276 80°C 30V VW-1
- RoHS(EU2015/863) and REACH Compliant
- PACKING:1PC/PE BAG+label

MATERIAL LIST:

NO.	PARTS NAME	SPECIFICATION DESCRIPTION	QT'Y	REMARK
⑥	SHIELDING	IRON SHELL SHIELDING	2	
⑤	DUST CAP	LD PE	2	
④	TUBE END	BLACK PVC 45P	2	
③	OUTER COVER	BLACK ABS ASSEMBLY TYPE	2	
②	CONNECTOR	DP 20P/M WITH LATCHING BLACK INSULATION, THE PIN GOLD PLATED ,THE SHELL FOR GOLD PLATED	2	
①	CABEL	DP1.4V CABLE[(30AWG TC)*1P+(30AWG TC)+FAM]*5+(30AWG TC)*4C+AL-FOIL+(30AWG BC)+BRAID, JACKET:PVC black OD:6.0±0.2mm	1	

ITEM NO	LENGTH
S215437V4	500±15
S215438V4	1000±20
S215439V4	1500±30
S215440V4	2000±30

SYNERGY21

NO.	PARTS NAME	SPECIFICATION DESCRIPTION	QT'Y	REMARK	CUSTOMER	ITEM NO.				
Alvan	Alvan	ADD NEW ITEMS	2020-09-05	A1	PRODUCT NAME	30AWG DisplayPort 1.4V Male-Male Black Cable Gold plating	manufacture country:	CHINA	UNIT	MM
		NEW	2019-09-06	A	DRAWNBY	CHECKBY	APPOBY	DATE		
BY	CHK	REVISION RECORD MODIFICATIONS	DATE	REV.	SYNERGY21	SYNERGY21	SYNERGY21	2019-09-06		