



NOTE:

1. Electrical test:
  - (1). 100% open short & miss wire test;
  - (2). Insulation resistance: DC 300V 0.1S 10MΩ;
  - (3). Conductor resistance: 3Ω Max;
  - (4). SSD TEST: 700MB/S (min)
2. Feature:
  - Full-featured USB3.2 Type-C Cable (USB3.2 Gen2x2)
  - Transmission rate Up to 20Gbps
  - Resolution up to 4k@60Hz
  - Backwards compatible with USB 3.1, 3.0 and 2.0 and Thunderbolt 3
  - Supports USB power delivery 3.1 (EPR 20V/5A-48V/5A) 240W
3. RoHS 2.0 and REACH Compliant
4. Packing: 1PC/SYNERGY 21 bag+label

MATERIAL LIST:

NO.	PARTS NAME	SPECIFICATION DESCRIPTION	QT' Y	REMARK
⑤	MOULDING	PVC Black	2	
④	E-mark	USB3.2 GEN2*2 20Gbps 240W/5A	2	
③	Housing	Aluminum housing Gray	2	
②	USB TYPE C	USB3.2 C/M Solder Type, Black PBT Insulation, The Pin Gold Plating, the shell for Nickel Plating With E-MARK	2	
①	CABLE	USB3.2 GEN2*2 CABLE[1P*29AWG+AL+MY]*4C+1P*32AWG+4C*32AWG+2C*23AWG+D+AM+B PVC JACKET BLACK OD: 4.8±0.2MM with Black Cotton braid OD: 5.2±0.2mm	1	

ITEM NO.	LENGTH (mm)
S215315	3000±50

SYNERGY 21					CUSTOMER		ITEM NO.		SEE THE CHART		
NEW					PRODUCT NAME		manufacture country:		CHINA	UNIT	MM
BY	CHK	REVISION RECORD MODIFICATIONS	DATE	REV.	SYNERGY 21	SYNERGY 21	SYNERGY 21	SYNERGY 21	DATE	2024-07-22	

					USB3.2 20Gbps EPR 240W USB Type C male -C male		CHINA				
					DRAWNBY		CHECKBY		APPOBY		
					SYNERGY 21		SYNERGY 21		SYNERGY 21		