








## DESKTOP UPS WITH AUTOMATIC VOLTAGE REGULATION



### The desktop UPS with automatic voltage regulation to offer power protection


Ideal for home and office applications, the BU Series adopts line-interactive topology with Automatic Voltage Regulation (AVR) function to offer stabilized AC power output. The products are compatible with generators to prolong power continuity. The UPSs also feature overload protection and configurable alarm to safeguard your devices. The desktop design with mounting slots allows users to place it easily on walls, desktop or other tight spaces.

#### SERIES FEATURES

- Line-interactive UPS Topology
- Automatic Voltage Regulation (AVR)
- Simulated Sine Wave Output
- Generator Compatible
- Overload Protection
- Surge and Spike Protection
- EMI and RFI Filtration
- LED Status Indicator
- Configurable Alarm
- Wall Mount Installation

#### PRODUCT CALLOUTS

1. Power On Indicator
2. Power On/Off Switch
3. Battery & Surge Protected Outlets
4. AC Input Power Cord
5. USB Port



BU650EU



## TECHNICAL SPECIFICATIONS

Model Name	BU650EU
<b>General</b>	
UPS Topology	Line-interactive
<b>Input</b>	
Generator Compatibility	Yes
Nominal Input Voltage (Vac)	230 ± 10%
Input Voltage Range (Vac)	165 - 280
Input Frequency (Hz)	50 ± 5, 60 ± 5
Input Frequency Detection	Auto-sensing
Rated Input Current (A)	2.95
Input Connector Type	Schuko
<b>Output</b>	
Capacity (VA)	650
Capacity (Watts)	360
On Battery Waveform	Simulated Sine Wave
On Battery Voltage(s) (Vac)	230 ± 10%
On Battery Frequency (Hz)	50 ± 1%, 60 ± 1%
Automatic Voltage Regulation (AVR)	Single Boost, Single Buck
Overload Protection	Fuse
Outlet(s) - Total	3
Outlet Type	Schuko x 3
Outlet(s) - Battery & Surge Protected	3
Typical Transfer Time (ms)	4
<b>Battery</b>	
Runtime at 60W (min)	30
Runtime at 90W (min)	18
Typical Recharge Time (Hours)	8
User Replaceable	No
Battery Type	Sealed Lead-acid
<b>Surge Protection &amp; Filtering</b>	
Surge Suppression (Joules)	150
EMI/RFI Filtration	Yes
<b>Management &amp; Communications</b>	
LED Indicators	Power On, Line Mode, Battery Mode, Low Battery
HID Compliant USB Port(s)	1
Audible Alarms	Battery Mode, Low Battery, Overload, UPS Fault
<b>Physical</b>	
Form Factor	Desktop
<b>Physical Size - UPS Module</b>	
Dimensions (WxHxD) (mm.)	158 x 91.5 x 240
Weight (kg.)	3.8
<b>Environmental</b>	
Operating Temperature (°C)	0 - 40
Operating Relative Humidity (Non-condensing) (%)	0 - 90
Online Thermal Dissipation (BTU/hr)	40
<b>Certifications</b>	
Certifications*	CE
RoHS	Yes

\*Certifications may vary according to different regions. Visit [www.cyberpower.com](http://www.cyberpower.com) for more information.  
 #All specifications are subject to change without notice.