



ALLNET

ALL-MC106-SC-SM

Medienconverter 10/100BaseTX to 100BaseFX/SC

- 1x 10/100BaseTX Ethernet TP Port
- 1x100BaseFX Ethernet Fiber Port Single Mode SC
- TP Port support Half/Full-Duplex, Auto-MDI/MDI-X and Auto-Negotiation
- FX Fiber Port support 1310nm Single Mode SC max. 20km
- Ethernet 802.3x Flow Control

Part-No. 105638

Note: Product specification is subject to change without notice.



| Item | Specification |
|---------------------|--|
| Standards: | IEEE 802.3 10BaseT IEEE 802.3u 100BaseTX/100BaseFX IEEE 802.3x FLOW Control |
| Features: | 1x 10/100BaseT with RJ-45 Connector 1x 100BaseFX with Fiber Connector SM,SC |
| Data Transfer Rate: | Ethernet: 10Mbps/Half-Duplex ; 20Mbps/Full-Duplex Fast Ethernet: 100Mbps/Half-Duplex; 200Mbps/Full-Duplex |
| Transmission Media: | 10BaseT Cat. 3, 4, 5 UTP/STP, bis zu 100 m 100BaseTX Cat. 5 UTP/STP, bis zu 100 m 100BaseFX 90/125µm1310nm Single Mode SC-Typ LWL, max 20 km |
| Led Indicators: | Power on Per Port:(TX): Link/Act, Speed, FDX/COL ; (FX): Link/Act, FDX/COL |
| Power Requirement: | DC 5V/2A external Power Supply included, Replace PSU = Part NO: 140858 |
| Power Consumption: | 2,5 Watts (Max) |
| Dimensions: | 94 × 71 × 26 mm (L x W x H) |
| Weight: | 230g (only MC) |
| Environment: | Temperature operating: 0 ~ 50 °C Humidity operating: 10% ~ 90% (non-condensing) Temperature storage: -20 ~ 70 °C Humidity storage: 10% ~ 90% (non-condensing) |
| Certifications: | CE |