



NOTE:

- 100% open short & miss wire test;
- RoHS 2.0 AND REACH compliant
- PRINTING: SUPER HIGH SPEED USB3.1 CABLE Exxxxxx 兄  
AWM 2725 32AWG×2P+30AWG×1P+24AWG×2C 80°C  
30V VW-1

MATERIAL LIST:

NO.	PARTS NAME	SPECIFICATION STANDARD	QT' Y	REMARK
⑤	OUTER MOLD	PVC color For black	2	
④	INNER MOLD	LD-PE	2	
③	USB TYPE A Male	USB Type A Male Type, blue insulation, The Pin Gold Plating, the shell for Nickel Plating	1	
②	USB TYPE C Male	USB Type C Male Solder Type, Black PBT Insulation, The Pin Gold Plating, the shell for Nickel Plating with 56KΩ resistance	1	
①	CABLE	USB 3.1 (32AWG TC*1P+E+AL+ML)*2+(30AWG TC*2C)+(24AWG TC*2C)+AB B=80# OD: 4.3±0.15mm JACKET: PVC/BLACK	1	

ITEM NO.	LENGTH	COLOUR	Emark	Current	Data
S215325V2	500±20MM	BLACK	W/O	Max 3A	Max 10G
S215326V2	1000±20MM	BLACK	W/O	Max 3A	Max 10G

NO.					PARTS NAME					SPECIFICATION STANDARD					QT' Y	REMARK		
NEW										2018-09-27					A			
BY	CHK	REVISION RECORD MODIFICATIONS								DATE	REV.	SYNERGY 21		SYNERGY 21		SYNERGY 21		2018-09-27