



NOTE:

- Electrical test:
 - 100% open short & miss wire test;
 - Insulation resistance:DC 300V 0.1S 10MΩ;
 - Conductor resistance:3Ω Max;
 - SSD TEST:700MB/S (min)
- Feature:
 - Full-featured USB3.2 Type-C Cable (USB3.2 Gen2x2)
 - Transmission rate Up to 20Gbps
 - Resolution up to 4k@60Hz
 - Backwards compatible with USB 3.1, 3.0 and 2.0 and Thunderbolt 3
 - Supports USB power delivery 3.1 (EPR 20V/5A-48V/5A) 240W
- RoHS 2.0 and REACH Compliant
- Packing:1PC/SYNERGY 21 bag+label

MATERIAL LIST:

NO.	PARTS NAME	SPECIFICATION DESCRIPTION	QT' Y	REMARK
⑤	MOULDING	PVC Black	2	
④	E-mark	USB3.2 GEN2*2 20Gbps 240W/5A	2	
③	Housing	Aluminum housing Gray	2	
②	USB TYPE C	USB3.2 C/M Solder Type,Black PBT Insulation,The Pin Gold Plating, the shell for Nickel Plating With E-MARK	2	
①	CABLE	USB3.2 GEN2*2 CABLE[1P*29AWG+AL+MY]*4C+1P*32AWG+4C*32AWG+2C*23AWG+D+AM+B PVC JACKET BLACK OD:4.8±0.2MM with Black Cotton braid OD:5.2±0.2mm	1	

ITEM NO.	UNO ITEM NO.	LENGTH(mm)
S215315	716010UX,03	3000±50

					UNO ELECTRONIC LIMITED (HK)						
					CUSTOMER	AN		ITEM NO.	SEE THE CHART		
					PRODUCT NAME	USB3.2 20Gbps EPR 240W USB Type C male -C male		UNO ITEM NO.	716010UX	UNIT	MM
					DATE	2024-07-22	AO	DRAWNBY	CHECKBY	APPOBY	DATE
BY	CHK	REVISION RECORD MODIFICATIONS			DATE		REV.	Gao	Alvan		2024-07-22